

AGRIFORCE HD



KRONOS RANGE

25 products | 16 SAE grades

SAE 5W-30	1	SAE 10W	2
SAE 10W-30	2	SAE 10W-40	2
SAE 15W-40	1	SAE 20W-30	1
SAE 20W-50	1	SAE 75W-90	1
SAE 80W	1	SAE 80W-90	1
SAE 85W-140	1	SAE 30	2
SAE 40	2	SAE 90	1
SAE 140	1	SAE 250	1

SPECIFICATIONS

API CJ-4/CI-4+/CI-4/CH-4	CUMMINS CES 20078 JASO
ACEA E7/E5	FH-1
DTFR 15B120 (MB 228.5)	VOLVO VDS-3
DTFR 15B110 (228.3)	RENAULT RVI RLD-2
MAN 3275-1 CATERPILLAR	Mack EO-N / EO-M / EO-M
ECF-2 / ECF-A	PLUS
MTU Type 3 -OIL TYPE 2 Deutz	SFU IVECO DH-1 18-1804 T2
DQC IV-10	E7

Lubricant for Agricultural, Construction & Earthmoving Machinery Diesel Engines

SAE 15W-40 lubricant for compatible diesel engines of agricultural, construction-site and earthmoving machinery. Intended for demanding duty cycles and operation under load; the specific emission specifications and approvals must be verified separately.

Key Advantages:

- Maximum oxidative stability
- Neutralisation of acids
- Protection against deposits, varnish and sludge
- Maximum thermal stability
- Maximum detergency
- Excellent dispersant, anti-corrosion and anti-rust properties



AVAILABLE PACKING

5 L	20 L
208 L	1.000 L

KRONOS

AGRIFORCE HD

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,88
Kinematic viscosity at 40°C	cSt	ASTM D445	110
Kinematic viscosity at 100°C	cSt	ASTM D445	15
Viscosity Index	-	ASTM D2270	142
Flash Point	°C	ASTM D92	236
Pour Point	°C	ASTM D97	-26

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."