

CHAINFORCE



KRONOS RANGE

25 products | 16 SAE grades

SAE 5W-30	1	SAE 10W	2
SAE 10W-30	2	SAE 10W-40	2
SAE 15W-40	1	SAE 20W-30	1
SAE 20W-50	1	SAE 75W-90	1
SAE 80W	1	SAE 80W-90	1
SAE 85W-140	1	SAE 30	2
SAE 40	2	SAE 90	1
SAE 140	1	SAE 250	1

SPECIFICATIONS

Biodegradabilità: OECD 301 B > 95%

Biodegradable Plant-Based Chain & Bar Lubricant for Chainsaws

Biodegradable lubricant of plant origin for chainsaw chains and bars, in total-loss lubrication systems. Intended for continuous lubrication and protection of the chain during work, not for mixing with two-stroke engine fuel.

Key Advantages:

- Anti-seize action
- Cooling function
- Adhesive action
- Anti-drip action
- Maximum anti-wear capacity



AVAILABLE PACKING

5 L	20 L
208 L	1.000 L

KRONOS

CHAINFORCE

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	920
Kinematic viscosity at 40°C	cSt	ASTM D445	35
Kinematic viscosity at 100°C	cSt	ASTM D445	7,93
Viscosity Index	-	ASTM D2270	208
Flash Point	°C	ASTM D92	280
Pour Point	°C	ASTM D97	-22

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."