

COOLTRON 10 BLUE OAT



X-STREAM RANGE

19 products | 5 grades

G11	6	G12	3
G12+	2	G12++	3
G13	3		

SPECIFICATIONS

Technology: OAT

Μέθοδοι δοκιμών

Υπερκαλύπτει μεθόδους ASTM αξιολόγησης των προστατευτικών ιδιοτήτων.

Στατική διάβρωση σε γαλβανισμένο δοχείο: ASTM D1384

Δυναμική διάβρωση: CUNA/MA/SC55 GdL 1

Συμβατότητα με ελαστομερή: CUNA NC 903-07

Διάβρωση λόγω σπληαίωσης με υπερήχους: ASTM D2966

Διάβρωση σε θερμή πλάκα αλουμινίου: ASTM D4340

Ready-to-Use OAT Monoethylene Glycol Antifreeze for Aluminium & Light Metal Engines

Ready-to-use monoethylene glycol antifreeze with OAT technology. For cooling circuits of internal combustion engines made of aluminium alloys and light metals.

Key Advantages:

- Good protection of aluminium alloy engine circuits
- High heat dissipation capacity
- Tracer to quickly detect leaks in the circuit
- NAP free (nitrate, amine and phosphate free)



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

X-STREAM

COOLTRON 10 BLUE OAT

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	ASTM D3306	BLUE
Appearance	-	ASTM D3306	Limpid
Density	kg/dm ³	ASTM D3306	1,03
pH (diluted)	-	ASTM D3306	8,5
Boiling point	°C	ASTM D1120	105
Freezing point	°C	ASTM D1177	-10
Glass corrosion test	mg/specimen	ASTM D1384	pass

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."