

COOLTRON 100 G11 BLUE IAT



X-STREAM RANGE

19 products | 5 grades

G11	6	G12	3
G12+	2	G12++	3
G13	3		

SPECIFICATIONS

Technology: IAT

CUNA NC 956-16 (I) VW G-11

BS 6580 (GB) FVV Heft R 443 (D) Afnor R 15/601 (F) ASTM D 3306 and 4985 JIS K 2234 (J) KSM 2142 (K) NATO S 759 UNE 26361-88 (E) EMPA (CH) E/L 1415c (MIL Italy)

CUMMINS CES 14603

Porsche / VW/Audi/Seat/Skoda TL 774 C G11

Mercedes DBL 7700

FIAT 9.55523/41

Concentrated IAT Monoethylene Glycol Antifreeze for Older Cast Iron & Ferrous Engines

Concentrated monoethylene glycol antifreeze, specifically for cooling circuits of older engines requiring IAT, with cast iron, iron, steel and ferrous metal blocks.

Key Advantages:

- Maximum protection of engine circuits with cast iron and ferrous components
- High heat dissipation capacity
- Tracer to quickly detect leaks in the circuit
- Excellent protection of the water pump and all rubber parts
- Raised boiling point



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

X-STREAM

COOLTRON 100 G11 BLUE IAT

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	ASTM D3306	Turchese/blu
Appearance	-	ASTM D3306	Limpid
Density	kg/dm ³	ASTM D3306	1,12
pH (50% dilution)	-	ASTM D3306	8,9
Boiling point	°C	ASTM D1120	197
Freezing point (50% dilution)	°C	ASTM D1177	-38
Glass corrosion test	mg/specimen	ASTM D1384	pass

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."