

COOLTRON 100 G13 PURPLE Si-OAT



X-STREAM RANGE

19 products | 5 grades

G11	6	G12	3
G12+	2	G12++	3
G13	3		

SPECIFICATIONS

Technology: Si-OAT

VW TL 774 J G13 ASTM D3306

OEM G013A8J1G GA13A8JM1

SKODA-VOLKSWAGEN – AUDI SEAT

MERCEDES-BENZ 000 989 28 25 / 000 989 28 25 11

PORSCHE 000 043 301 47

Concentrated Si-OAT Glycerine/Glycol Antifreeze for Hybrid, Electric & Combustion Vehicles

Concentrated glycerine and ethylene glycol antifreeze for indirect cooling circuits of hybrid and fully electric vehicles and of internal combustion engines in VAG Group passenger/commercial vehicles. The TDS refers to organic inhibitors and silicates. For indirect cooling; not to be generalised to direct battery immersion.

Key Advantages:

- Maximum protection of cast iron, iron and aluminium alloy engine circuits
- High heat dissipation capacity
- Tracer to quickly detect any leaks in the circuit
- Excellent protection of the circuit and all rubber parts
- Raised boiling point



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

X-STREAM

COOLTRON 100 G13 PURPLE Si-OAT

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	ASTM D3306	Purple
Appearance	-	ASTM D3306	Limpid
Density	kg/dm ³	ASTM D3306	1,13
pH (50% dilution)	-	ASTM D3306	8,4
Boiling point	°C	ASTM D1120	197
Freezing point (50% dilution)	°C	ASTM D1177	-36
Glass corrosion test	mg/specimen	ASTM D1384	pass

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."