

COOLTRON 20 G11 GREEN OAT



X-STREAM RANGE

19 products | 5 grades

G11	6	G12	3
G12+	2	G12++	3
G13	3		

SPECIFICATIONS

Technology: OAT
 BS 6580 AFNOR R15-601
 ASTM D 3306/D4985
 PORSCHE / VW / AUDI / SEAT /
 SKODA TL 774C
 FORD FSD M97 B49-A
 GM US 6277M
 FORD ESD M97 B49-A
 CHRYSLER MS 9176
 Υπερκαλύπτει μεθόδους ASTM
 αξιολόγησης των
 προστατευτικών ιδιοτήτων.

Στατική διάβρωση σε γυάλινο
 δοχείο: ASTM D1384
 Δυναμική διάβρωση:
 CUNA/MA/SC55 GdL 1
 Συμβατότητα με ελαστομερή:
 CUNA NC 903-07
 Διάβρωση λόγω σπληαίωσης με
 υπερήχους: ASTM D2966
 Διάβρωση σε θερμή πλάκα
 αλουμινίου: ASTM D4340

Ready-to-Use OAT Coolant for Aluminium and Light-Metal Engine Cooling Circuits

Ready-to-use OAT monoethylene glycol coolant for engine circuits containing aluminium and light metals.

Key Advantages:

- Good protection of aluminium-alloy engine circuits
- High heat dissipation capacity
- Tracer to quickly detect leaks in the circuit
- NAP-free (nitrate, amine and phosphate free)



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

X-STREAM

COOLTRON 20 G11 GREEN OAT

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	ASTM D3306	BLUE
Appearance	-	ASTM D3306	Limpid
Density	kg/dm ³	ASTM D3306	1,04
pH (diluted)	-	ASTM D3306	8,5
Boiling point	°C	ASTM D1120	107
Freezing Point	°C	ASTM D1177	-20
Glass corrosion test	mg/specimen	ASTM D1384	pass

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."