

DIESEL POWER 10W-40 CNG



HERCULES RANGE

14 products | 8 SAE grades

SAE 0W-20	1	SAE 5W-20	1
SAE 5W-30	3	SAE 5W-40	1
SAE 10W-30	1	SAE 10W-40	2
SAE 15W-40	4	SAE 20W-50	1

SPECIFICATIONS SAE 10W-40

API CK-4/ CJ-4/CI-4+/CI-4/CH-4	MACK E0S 4.5
ACEA E11/E9/E8/E6/E4	RENAULT RVI RLD-3 / RLD-4
DTFR 15C100 (MB 228.31),	CUMMINS CES 20081/
DTFR 15C110 (MB 228.51),	CES20086 JASO DH-2
DTFR 15C120 (MB 228.52)	DEUTZ DQC III-10-LA/DQC IV-
DETROIT 93 K222 SFU IVECO	18-LA
18-1804 TLS CK4	MTU
CATERPILLAR ECF-3	CAT Type 2.1/3.1
SCANIA LA	SFU IVECO
MAN 3271-1/3477/3775	CAT TLS CK-4 IVECO 18-809
VOLVO VDS-4.5	CLASSE NG2
VOLVO CNG	

Synthetic Lubricant for Heavy-Duty CNG Commercial Vehicle Engines

Synthetic SAE 10W-40 lubricant for heavy-duty commercial vehicle engines running on CNG and other applications explicitly approved in the TDS. The specialised formulation aims at lubricating protection in extended operation and resistance to thermal stress.

Key Advantages:

- Maximum action against the molecular oxidation of the lubricant
- Effective prevention of deposit formation
- Maximum thermal stability
- Maximum detergency
- High dispersancy, anticorrosion and antirust properties



AVAILABLE PACKING

5 L	20 L
60 L	208 L
1.000 L	

HERCULES

DIESEL POWER 10W-40 CNG

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,862
Kinematic viscosity at 40°C	cSt	ASTM D445	96,0
Kinematic viscosity at 100°C	cSt	ASTM D445	15,0
Viscosity Index	-	ASTM D2270	164
Flash Point	°C	ASTM D92	231
Pour Point	°C	ASTM D97	-30

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."