

DIESEL POWER 15W-40 CNG



HERCULES RANGE

14 products | 8 SAE grades

SAE 0W-20	1	SAE 5W-20	1
SAE 5W-30	3	SAE 5W-40	1
SAE 10W-30	1	SAE 10W-40	2
SAE 15W-40	4	SAE 20W-50	1

SPECIFICATIONS SAE 15W-40

API CF-4	ISUZU CNG DAILY CNG
MB 226.9	VOLVO CNG
MAN 3271-1	CUMMINS 20085 20074
SFU :	CUMMINS 20092
RENAULT RGD HYUNDAI CNG	DETROIT DIESEL 93K216

Synthetic Lubricant for Professional CNG Gas Engines

Synthetic SAE 15W-40 lubricant for professional CNG gas engines where this viscosity grade is specified. The specialised formulation aims at stable lubrication and engine protection during prolonged operation under load.

Key Advantages:

- Anti-oxidation action against molecular degradation of the lubricant
- Action against fouling, especially on spark plugs
- Maximum thermal stability
- Maximum detergency
- High dispersant, anticorrosion and antirust properties



AVAILABLE PACKING

5 L	20 L
60 L	208 L
1.000 L	

HERCULES

DIESEL POWER 15W-40 CNG

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,87
Kinematic viscosity at 40°C	cSt	ASTM D445	98,1
Kinematic viscosity at 100°C	cSt	ASTM D445	14,6
Viscosity Index	-	ASTM D2270	154
Flash Point	°C	ASTM D92	233
Pour Point	°C	ASTM D97	-29

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."