

DIESEL TECH 10W-30 LS



HERCULES RANGE

14 products | 8 SAE grades

SAE 0W-20	1	SAE 5W-20	1
SAE 5W-30	3	SAE 5W-40	1
SAE 10W-30	1	SAE 10W-40	2
SAE 15W-40	4	SAE 20W-50	1

SPECIFICATIONS SAE 10W-30

API CK-4/ CJ-4/CI-4+/CI-4/CH-4	VOLVO VDS-3
ACEA E11/E9/E8/E6	MACK E0-0 PP/ EO-M+
DTFR 15C100 (MB 228.31)	RENAULT RLD-3 / RLD-2
DETROIT 93	CUMMINS CES 20081/86/92
K218/K215/K214/K222	DEUTZ DQC III-10-LA/DQC IV-
CATERPILLAR ECF-2/ECF-3	18-LA
MAN 3575/3775	MTU
VOLVO VDS-4	CAT 2.1/3.1

Low SAPS Synthetic-Based Multigrade Lubricant for Professional Heavy-Duty Diesel Engines

Synthetic-based multigrade SAE 10W-30 lubricant with Low SAPS technology for professional heavy-duty diesel engines. The formulation focuses on lubricating protection under load and compatibility with the specified exhaust after-treatment systems.

Key Advantages:

- Low friction for better protection
- Counteraction against the molecular oxidation of the lubricant
- Maximum thermal stability
- Maximum detergency
- High dispersancy, anticorrosion and antirust properties



AVAILABLE PACKING

5 L	20 L
60 L	208 L
1.000 L	

HERCULES

DIESEL TECH 10W-30 LS

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,858
Kinematic viscosity at 40°C	cSt	ASTM D445	84,2
Kinematic viscosity at 100°C	cSt	ASTM D445	14,2
Viscosity Index	-	ASTM D2270	175
Flash Point	°C	ASTM D92	229
Pour Point	°C	ASTM D97	-35

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."