

ELITE TECH 0W-30 C3



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 0W-30

API SN/CF
 ACEA C3
 MB 229.31
 MB 229.51
 MB 229.52
 RENAULT RN 0700 RN 0710
 PSA B71 2312
 FIAT 9.5555-GS1
 FIAT 9.55535-DS1

Synthetic Controlled-SAPS Lubricant for Engines Requiring ACEA C3

Synthetic SAE 0W-30 with a stated Group IV base, for engines requiring ACEA C3. The controlled-SAPS formulation is intended for compatible after-treatment systems, combining lubricating protection and stability under demanding conditions.

Key Advantages:

- Low friction coefficient
- Reduced pollutant emissions
- Superior oxidative stability at the high operating temperatures of modern turbocharged engines
- Low pour point and very high viscosity index for protection across wide temperature changes
- Excellent anti-corrosion, anti-rust and cleaning properties



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

ELITE TECH 0W-30 C3

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,850
Kinematic viscosity at 40°C	cSt	ASTM D445	63,1
Kinematic viscosity at 100°C	cSt	ASTM D445	11,1
Viscosity Index	-	ASTM D2270	170
Flash Point	°C	ASTM D92	226
Freezing point	°C	ASTM D97	-43

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."