

ELITE TECH 5W-30 A3/B4



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 5W-30

API SN
 ACEA A3/B4
 MB 229.3
 MB 229.5
 MB 226.5
 GM LL-A-025
 GM LL-B-025
 VW 502.00/505.00
 RN 0700 RN 0710

Synthetic Full-SAPS Lubricant for Demanding Petrol & Diesel Engines

Synthetic SAE 5W-30 lubricant with Full SAPS technology for compatible engines requiring ACEA A3/B4. It is intended for demanding petrol and diesel applications, including turbocharged engines, with an emphasis on protection against wear.

Key Advantages:

- Exceptional oxidation stability at the high operating temperatures of modern turbocharged engines
- High cleaning performance
- Effective acid neutralisation
- Low pour point



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

ELITE TECH 5W-30 A3/B4

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,856
Kinematic viscosity at 40°C	cSt	ASTM D445	62,0
Kinematic viscosity at 100°C	cSt	ASTM D445	10,8
Viscosity Index	-	ASTM D2270	167
Flash Point	°C	ASTM D92	228
Freezing point	°C	ASTM D97	-36

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."