

ELITE TECH 5W-30 C3



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 5W-30

API SP/SN PLUS
 ACEA C3
 BMW LL-04
 MB 229.51
 MB 229.52
 OPEL OV 0401547
 RENAULT RN 0700 RN 0710
 STELLANTIS FPW9.55535/03
 PSA B712290/PSA B712297

Synthetic Mid-SAPS Lubricant for Petrol & Diesel Engines with Particulate Filters

Synthetic SAE 5W-30 lubricant with ACEA C3 / Mid SAPS technology for compatible petrol and diesel engines with particulate filters. Designed to balance lubricating protection, oxidation stability and the limitation of harmful residues in after-treatment systems.

Key Advantages:

- Excellent oxidation stability
- Superior cleanliness
- Low friction
- Low pour point and very high viscosity index for protection across a wide temperature range
- Low sulphur, phosphorus and sulphated ash content



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

ELITE TECH 5W-30 C3

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,852
Kinematic viscosity at 40°C	cSt	ASTM D445	67,1
Kinematic viscosity at 100°C	cSt	ASTM D445	11,3
Viscosity Index	-	ASTM D2270	165
Flash Point	°C	ASTM D92	229
Freezing point	°C	ASTM D97	-35

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."