

ELITE TECH 5W-40 C4 LS



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 5W-40

API SN/CF
ACEA C4
MB 226.51
RENAULT RN 0720

Synthetic Low-SAPS Lubricant for Petrol & Diesel Engines Requiring ACEA C4

Synthetic SAE 5W-40 lubricant with Low SAPS technology for compatible petrol and diesel engines with ACEA C4 requirements. The formulation, with reduced sulphated ash, phosphorus and sulphur content, helps protect particulate filters and catalytic systems.

Key Advantages:

- Compatibility with FAP, DPF, SCR, TWC and EGR technologies
- Low sulphur, phosphorus and sulphated ash content
- Low friction
- Low pour point and very high viscosity index for protection across wide temperature changes
- Excellent anti-corrosion, anti-rust and cleaning properties



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

ELITE TECH 5W-40 C4 LS

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,859
Kinematic viscosity at 40°C	cSt	ASTM D445	91
Kinematic viscosity at 100°C	cSt	ASTM D445	14,5
Viscosity Index	-	ASTM D2270	166
Flash Point	°C	ASTM D92	229
Freezing point	°C	ASTM D97	-34

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."