

ELITE TECH 5W-40 DUAL GAS



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 5W-40

API SP/SN PLUS	RN 0700/0710
ACEA C3	OPEL OV 0401547
MB 229.31	BMW LL-04
MB 229.51	FIAT 9.55535-T2
MB 229.52	FIAT 9.55535-S2

Synthetic Lubricant for Dual-Fuel Petrol/LPG & CNG Engines

Synthetic SAE 5W-40 for compatible dual-fuel petrol/LPG or CNG engines, naturally aspirated or turbocharged. The formulation is geared towards lubricating protection during operation on gaseous fuels and towards thermal and oxidative stability.

Key Advantages:

- Protection of valve stems
- High thermo-oxidative stability
- Resistance to viscosity increase
- High dispersancy
- Excellent anti-corrosion, anti-rust and cleaning properties



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

ELITE TECH 5W-40 DUAL GAS

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,853
Kinematic viscosity at 40°C	cSt	ASTM D445	88,2
Kinematic viscosity at 100°C	cSt	ASTM D445	15,0
Viscosity Index	-	ASTM D2270	179
Flash Point	°C	ASTM D92	233
Freezing point	°C	ASTM D97	-35

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."