

FLEXI 20W-60



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 20W-60

API SL/SG/CD
ACEA A3/B4
VW 501.01/505.0

High-Viscosity Lubricant for Passenger Car & Light Commercial Engines in Demanding Use

High-viscosity SAE 20W-60 lubricant for compatible engines of passenger cars and light commercial vehicles under demanding conditions. It focuses on consistent lubricating protection during hot operation, in engines where this viscosity grade is permitted.

Key Advantages:

- High detergency
- Acid-neutralising function
- Protection of mechanical components
- High thermal dissipation capacity
- Prevention of sludge and emulsions



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

FLEXI 20W-60

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,87
Kinematic viscosity at 40°C	cSt	ASTM D445	172,0
Kinematic viscosity at 100°C	cSt	ASTM D445	24,0
Viscosity Index	-	ASTM D2270	170
Flash Point	°C	ASTM D92	232
Freezing point	°C	ASTM D97	-25

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."