

FLEXI MONO SAE 40



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE SAE 40

API SL/CF

Monograde Lubricant for Older Petrol & Diesel Cars and Light Commercial Vehicles

Monograde SAE 40 lubricant for compatible petrol and diesel engines, mainly of older passenger cars and light commercial vehicles. Intended for applications where the manufacturer specifies a monograde SAE 40, with an emphasis on basic lubricating protection.

Key Advantages:

- High detergency
- Acid-neutralising function
- Protection of mechanical components
- Prevention of sludge and emulsions



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

FLEXI MONO SAE 40

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,88
Kinematic viscosity at 40°C	cSt	ASTM D445	135
Kinematic viscosity at 100°C	cSt	ASTM D445	15
Viscosity Index	-	ASTM D2270	113
Flash Point	°C	ASTM D92	231
Freezing point	°C	ASTM D97	-27

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."