

FLEXI MONO SAE 50



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE SAE 50

API SL/CF

Monograde Lubricant for Passenger Car & Light Commercial Vehicle Engines

Monograde SAE 50 lubricant for compatible engines of passenger cars and light commercial vehicles. Suitable exclusively for applications that specify SAE 50, with an emphasis on maintaining the lubricating film at high operating temperatures.

Key Advantages:

- High detergency
- Acid-neutralising function
- Protection of mechanical components
- High thermal dissipation capacity



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

FLEXI MONO SAE 50

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,892
Kinematic viscosity at 40°C	cSt	ASTM D445	185
Kinematic viscosity at 100°C	cSt	ASTM D445	18,5
Viscosity Index	-	ASTM D2270	112
Flash Point	°C	ASTM D92	234
Freezing point	°C	ASTM D97	-25

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."