

FOOD TECH FG 32



FOOD TECH RANGE

4 products | 4 ISO VG grades

ISO VG 32	1	ISO VG 46	1
ISO VG 68	1	ISO VG 220	1

SPECIFICATIONS ISO VG 32

ISO VG 32

Formulato con prodotti approvati FDA 21 CFR 178.3620(b) NSF H1

Special Lubricant for Food, Cosmetic and Pharmaceutical Production Plants

Special lubricant for food, cosmetic and pharmaceutical plants with controlled-production requirements. Suitability for specific contact is assessed on the basis of the documentation.

Key Advantages:

- Chemical inertness
- Maximum oxidation stability
- Hydrolytic stability
- Excellent material compatibility
- High anti-corrosion and anti-rust properties
- High anti-foaming capacity



AVAILABLE PACKING

20 L	208 L
1.000 L	

FOOD TECH

FOOD TECH FG 32

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	830
Kinematic viscosity at 40°C	cSt	ASTM D445	34
Kinematic viscosity at 100°C	cSt	ASTM D445	6,56
Viscosity index	-	ASTM D2270	150
Flash Point	°C	ASTM D92	248
Pour Point	°C	ASTM D97	-50

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."