

HERITAGE 2T



KRONOS RANGE

25 products | 16 SAE grades

SAE 5W-30	1	SAE 10W	2
SAE 10W-30	2	SAE 10W-40	2
SAE 15W-40	1	SAE 20W-30	1
SAE 20W-50	1	SAE 75W-90	1
SAE 80W	1	SAE 80W-90	1
SAE 85W-140	1	SAE 30	2
SAE 40	2	SAE 90	1
SAE 140	1	SAE 250	1

SPECIFICATIONS

API TC

JASO FD/ ISO-L-EGD TISI

Two-Stroke Lubricant for Air-Cooled Garden & Outdoor Equipment Engines

Lubricant for compatible air-cooled two-stroke engines of garden and outdoor equipment, such as chainsaws and brush cutters. Intended for applications where two-stroke cycle lubrication is specified, with the mixing ratio defined by the manufacturer.

Key Advantages:

- Stable and homogeneous mixtures with all types of gasoline
- Clean combustion without deposits
- Maximum cleanliness of the combustion chamber
- Excellent oxidation stability



AVAILABLE PACKING

5 L	20 L
208 L	1.000 L

KRONOS

HERITAGE 2T

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,88
Kinematic viscosity at 40°C	cSt	ASTM D445	49
Kinematic viscosity at 100°C	cSt	ASTM D445	8,5
Viscosity Index	-	ASTM D2270	151
Flash Point	°C	ASTM D92	146
Pour Point	°C	ASTM D97	-30

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."