

HYDRO TECH ECO HEES 46



CALYPSO RANGE

15 products | 3 ISO VG grades

ISO VG 32	5	ISO VG 46	5
ISO VG 68	5		

SPECIFICATIONS ISO VG 46

ISO VG 46
ECOLABEL CONTRATTO N° IT/027/008/001
DIN ISO 15380 HEES
SFU PARKER DENISON HF-1/HF-2/HF-6
SFU EATON BROCHURE 3-401/2010

Environmentally Compatible HEES Hydraulic Fluid ISO VG 46 with High Biodegradability

ISO VG 46 hydraulic fluid for applications requiring increased environmental compatibility, with low aquatic toxicity and high biodegradability according to the corresponding manufacturer description. Intended for compatible hydraulic circuits, selected according to the manufacturer's instructions.

Key Advantages:

- High biodegradability and low aquatic toxicity
- High viscosity index, to operate even under severe temperature changes
- Maximum oxidation stability
- Hydrolytic stability
- High anti-corrosion and anti-rust properties
- High anti-foaming capacity



AVAILABLE PACKING

5 L	20 L
208 L	1.000 L

CALYPSO

HYDRO TECH ECO HEES 46

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	902
Kinematic viscosity at 40°C	cSt	ASTM D445	49,9
Kinematic viscosity at 100°C	cSt	ASTM D445	11
Viscosity index	-	ASTM D2270	221
Flash Point	°C	ASTM D92	277
Pour point	°C	ASTM D97	<-15

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."