

HYDRO TECH ECO HEES 68



CALYPSO RANGE

15 products | 3 ISO VG grades

ISO VG 32	5	ISO VG 46	5
ISO VG 68	5		

SPECIFICATIONS ISO VG 68

ISO VG 68

ECOLABEL CONTRATTO N° IT/027/008/001

DIN ISO 15380 HEES

SFU PARKER DENISON HF-1/HF-2/HF-6

SFU EATON BROCHURE 3-401/2010

Environmentally Compatible HEES Hydraulic Fluid ISO VG 68 with High Biodegradability

ISO VG 68 hydraulic fluid for applications requiring increased environmental compatibility, with low aquatic toxicity and high biodegradability according to the corresponding manufacturer description. Intended for compatible hydraulic circuits, selected according to the manufacturer's instructions.

Key Advantages:

- High biodegradability and low aquatic toxicity
- High viscosity index, to operate even under severe temperature changes
- Maximum oxidation stability
- Hydrolytic stability
- High anti-corrosion and anti-rust properties
- High anti-foaming capacity



AVAILABLE PACKING

5 L	20 L
208 L	1.000 L

CALYPSO

HYDRO TECH ECO HEES 68

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	905
Kinematic viscosity at 40°C	cSt	ASTM D445	71,9
Kinematic viscosity at 100°C	cSt	ASTM D445	14,5
Viscosity index	-	ASTM D2270	213
Flash Point	°C	ASTM D92	296
Pour point	°C	ASTM D97	<-12

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."