

HYDRO TECH SYN HVI 68



CALYPSO RANGE

15 products | 3 ISO VG grades

ISO VG 32	5	ISO VG 46	5
ISO VG 68	5		

SPECIFICATIONS ISO VG 68

ISO VG 68
DIN 51524 PART 3 HVLP ISO 6743-4 ISO-L-HV/HS ISO 11158 HV
US Parker Denison HF-0/1/2 Level
Fives Cincinnati P69 (ISO 68) BS4231 HSE EATON VICKERS I-286/M2950-S
Eaton Brochure 03-401-2010 SAE MS1004 SAWER -DANFOSS
GM LS-2
U.S. STEEL 127/136 BOSCH REXROTH RDE 90220 LINDE AISE
127 AFNOR NF 48603 HV

Fully Synthetic HVI Hydraulic Fluid ISO VG 68 for Demanding Hydraulic Circuits

Fully synthetic HVI hydraulic fluid, ISO VG 68, for demanding hydraulic circuits with pressure and temperature variations. The formulation is designed for high antioxidant protection, according to the corresponding factory description. Use requires conformity with the technical requirements of the equipment.

Key Advantages:

- Very high viscosity index, to operate even with large temperature fluctuations
- Maximum oxidation stability
- High anti-corrosion and anti-rust properties
- High anti-foaming capacity
- Excellent pumpability at low temperatures



AVAILABLE PACKING

5 L	20 L
208 L	1.000 L

CALYPSO

HYDRO TECH SYN HVI 68

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	858
Kinematic viscosity at 40°C	cSt	ASTM D445	68
Kinematic viscosity at 100°C	cSt	ASTM D445	11,0
Viscosity index	-	ASTM D2270	153
Flash Point	°C	ASTM D92	242
Pour point	°C	ASTM D97	-48

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."