

INDUSTRIAL COOL 68 A/C



INDUSTRIAL RANGE

28 products | 10 ISO VG grades

ISO VG 20	1	ISO VG 32	2
ISO VG 46	2	ISO VG 68	5
ISO VG 100	1	ISO VG 150	4
ISO VG 220	3	ISO VG 320	2
ISO VG 460	2	ISO VG 680	2

SPECIFICATIONS ISO VG 68

ISO VG 68 ISO 6743/3 DRE
DIN 51503 KD
ISO DRE
DIN KE GAS (R134a-R404a-R507)

Special Lubricant for Refrigeration and Air-Conditioning Compressors

Special fluid for compressor applications.

Key Advantages:

- No formation of emulsions or sludge with traces of condensation
- Compatibility with all seals and metals
- Low pour point to remain fluid at the low temperatures of refrigeration circuits
- Protection against corrosion

AVAILABLE PACKING

20 L	208 L
1.000 L	

INDUSTRIAL

INDUSTRIAL COOL 68 A/C

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	950
Kinematic viscosity at 40°C	cSt	ASTM D445	68
Kinematic viscosity at 100°C	cSt	ASTM D445	8.5
Viscosity index	-	ASTM D2270	94
Flash Point	°C	ASTM D92	250
Pour Point	°C	ASTM D97	-40

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."