

INDUSTRIAL GEAR EP 220



INDUSTRIAL RANGE

28 products | 10 ISO VG grades

ISO VG 20	1	ISO VG 32	2
ISO VG 46	2	ISO VG 68	5
ISO VG 100	1	ISO VG 150	4
ISO VG 220	3	ISO VG 320	2
ISO VG 460	2	ISO VG 680	2

SPECIFICATIONS ISO VG 220

ISO VG 220 AGMA 5EP
AGMA 9005 E02
DIN 51517 part 3 CLP
ISO 12925-1 CKC/CKD
ISO 6743-5 CKC/CKD
GB5903
AIST 224 US Steel 224
CINCINNATI MILACRON P74
DAVID BROWN S1.53.101 E

Mineral EP Gear Oil for Industrial Gearboxes in Severe Conditions

Gears and gearboxes. Mineral lubricant with anti-friction properties to limit micropitting. Recommended for the protection of industrial machinery and mechanical devices under particularly severe conditions.

Key Advantages:

- Protection against micropitting
- Excellent thermo-oxidative stability
- Maximum EP protection



AVAILABLE PACKING

20 L	208 L
1.000 L	

INDUSTRIAL

INDUSTRIAL GEAR EP 220

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	878
Kinematic viscosity at 40°C	cSt	ASTM D445	220
Kinematic viscosity at 100°C	cSt	ASTM D445	19,2
Viscosity index	-	ASTM D2270	100
Flash Point	°C	ASTM D92	237
Pour Point	°C	ASTM D97	-24
FZG scuffing test A/8,3/90	-	ISO 14635-1	12+

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."