

INDUSTRIAL GEAR SYN EP 680



INDUSTRIAL RANGE

28 products | 10 ISO VG grades

ISO VG 20	1	ISO VG 32	2
ISO VG 46	2	ISO VG 68	5
ISO VG 100	1	ISO VG 150	4
ISO VG 220	3	ISO VG 320	2
ISO VG 460	2	ISO VG 680	2

SPECIFICATIONS ISO VG 680

ISO VG680 AGMA 8EP	AGMA 9005-E02
ISO 12925-1	GB5903
(CKC)/CKD/CKE/CKSMP	CINCINNATI MILACRON P35
ISO 6743-6	DAVID BROWN S1.53.101 E
(CKC)/CKD/CKE/CKSMP	SIEMENS FLENDER Rev. 15
DIN 51517 part 3 CLP -HC	level
US Steel 224 AIST 224	

Synthetic EP Gear Oil for Industrial Gears and Gearboxes

Synthetic EP 680 lubricant for gears and gearboxes.

Key Advantages:

- Excellent thermal and oxidative stability
- Reduced friction
- Excellent anti-wear performance
- High anti-corrosion and anti-rust properties
- High anti-foaming capacity
- Extended oil change intervals



AVAILABLE PACKING

20 L	208 L
1.000 L	

INDUSTRIAL

INDUSTRIAL GEAR SYN EP 680

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	859
Kinematic viscosity at 40°C	cSt	ASTM D445	680
Kinematic viscosity at 100°C	cSt	ASTM D445	56,6
Viscosity index	-	ASTM D2270	145
Flash Point	°C	ASTM D92	257
Pour Point	°C	ASTM D97	-33
FZG scuffing test A/8,3/90	-	ISO 14635-1	13+

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."