

INDUSTRIAL RELEASE 10/18



INDUSTRIAL RANGE

28 products | 10 ISO VG grades

ISO VG 20	1	ISO VG 32	2
ISO VG 46	2	ISO VG 68	5
ISO VG 100	1	ISO VG 150	4
ISO VG 220	3	ISO VG 320	2
ISO VG 460	2	ISO VG 680	2

SPECIFICATIONS

Casseri in legno dil 1:20 r 150m²/LCasseri in ferro dil 1:5 r 50 m²/L

Synthetic Water-Dilutable Release Agent for Precast Concrete Elements

Formwork release agent. Synthetic release agent for precast concrete elements. Used at concentrations of 5–20% for aqueous emulsions, applied by spraying, brushing or dipping.

Key Advantages:

- Synthetic release agent for precast concrete elements
- Dilutable at 5–20% to form aqueous emulsions
- Applicable by spraying, brushing or dipping



AVAILABLE PACKING

20 L	208 L
1.000 L	

INDUSTRIAL

INDUSTRIAL RELEASE 10/18

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	900
Appearance	-	Visual	Limpid
pH (50% in water)	-	ASTM E70	7,5
Dispersion in water	-	-	Lactescent emulsion

MODE OF USE

It disperses readily in water, resulting in a stable emulsion even in hard water. Add the fluid to the water and not vice versa to avoid the formation of non-emulsified parts. Apply a light spray coat. Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the MSDS. Additional information on MSDS. The aromatic polynuclear content is below the detection limit (50 ppb). Operators are not subject to periodic inspections for risk No. 47 (Ministerial Decree 303/1956).



"Blended with British Traditional Crafts."