

INDUSTRIAL THERMO QA



INDUSTRIAL RANGE

28 products | 10 ISO VG grades

ISO VG 20	1	ISO VG 32	2
ISO VG 46	2	ISO VG 68	5
ISO VG 100	1	ISO VG 150	4
ISO VG 220	3	ISO VG 320	2
ISO VG 460	2	ISO VG 680	2

SPECIFICATIONS

ISO 6743/12 QB

High-Efficiency Heat Transfer Fluid for Industrial Thermal Systems

Heat transfer systems. High-energy-efficiency heat transfer fluid, for maximising energy efficiency and precise temperature control throughout the plant.

Key Advantages:

- High heat transfer coefficient
- High chemical stability
- High thermal-oxidative stability
- Protection of the system against corrosion
- High demulsibility
- Fast air release



AVAILABLE PACKING

20 L	208 L
1.000 L	

INDUSTRIAL

INDUSTRIAL THERMO QA

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Appearance	-	Visual	limpid
Density at 15°C	kg/m ³	ASTM D1298	850
Kinematic viscosity at 40°C	cSt	ASTM D445	30
Kinematic viscosity at 100°C	cSt	ASTM D445	6,0
Flash Point	°C	ASTM D92	241
Pour Point	°C	ASTM D97	-40

MODE OF USE

Use according to the recommendations in the user and maintenance manual provided by the manufacturer. In open systems use up to a maximum temperature of 180°C, as the presence of air alters the oxidative stability of the product. Store the product in a cool, dry place, away from direct sunlight and at temperatures not exceeding 60°C.

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."