

INDUSTRIAL TOOL 150



INDUSTRIAL RANGE

28 products | 10 ISO VG grades

ISO VG 20	1	ISO VG 32	2
ISO VG 46	2	ISO VG 68	5
ISO VG 100	1	ISO VG 150	4
ISO VG 220	3	ISO VG 320	2
ISO VG 460	2	ISO VG 680	2

SPECIFICATIONS ISO VG 150

ISO VG 150 DIN 51502 CGLP
 ISO-L-CKC, ISO-L-CKE
 ISO 6743-6
 ISO 12925-1
 ISO-L-HG), ISO-L-HM
 ISO 6743-4
 ISO 11158
 CINCINNATI MILACRON (ISO VG 150)
 STANIMUC G 150

Total-Loss Slideway Lubricant for Machine Tools with Anti-Stick-Slip Properties

Slideways and slides. Total-loss lubricant for slideways and slides of machine tools and other machinery, with enhanced lubricity to prevent stick-slip.

Key Advantages:

- Optimum friction coefficient preventing judder (no stick-slip)
- Anti-drip function
- Maximum adhesiveness
- Maximum load resistance
- Excellent circuit protection
- High chemical stability and extended service life



AVAILABLE PACKING

20 L	208 L
1.000 L	

INDUSTRIAL

INDUSTRIAL TOOL 150

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,875
Kinematic viscosity at 40°C	cSt	ASTM D445	150
Freezing Point	°C	ASTM D7	-15

MODE OF USE

Use according to the recommendations in the user and maintenance manual provided by the manufacturer. Store the product in a cool, dry place, out of direct sunlight and at temperatures not exceeding 60°C.

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."