

INDUSTRIAL TOOL 68



INDUSTRIAL RANGE

28 products | 10 ISO VG grades

ISO VG 20	1	ISO VG 32	2
ISO VG 46	2	ISO VG 68	5
ISO VG 100	1	ISO VG 150	4
ISO VG 220	3	ISO VG 320	2
ISO VG 460	2	ISO VG 680	2

SPECIFICATIONS ISO VG 68

DIN 51502 CGLP
 ISO 6743-13 ISO 19378 ISO-L-GB ISO-L-GA
 ISO 12925-1 ISO 6743-6 ISO-L-CKC ISO-L-CKE
 ISO 6743-4 ISO 11158 ISO -L-HM
 CINCINNATI MILACRON P47 (ISO VG 68)
 STANIMUC G 68

Slideway and Hydraulic Lubricant for Machine Tools, Lifts and Hoists

Slideways and slides. Lubricant for circulation or total-loss systems, for hydraulic applications and loaded slideways/slides of machine tools, machinery, lifts and goods hoists. Special additives provide anti-stick properties and reduced dripping.

Key Advantages:

- Multifunctionality (slideway function combined with hydraulic and gear functions)
- Anti-drip
- Anti-friction
- No stick-slip
- EP protection



AVAILABLE PACKING

20 L	208 L
1.000 L	

INDUSTRIAL

INDUSTRIAL TOOL 68

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	865
Kinematic viscosity at 40°C	cSt	ASTM D445	68
Kinematic viscosity at 100°C	cSt	ASTM D445	9.1
Viscosity index	-	ASTM D2270	109
Flash Point	°C	ASTM D92	235
Pour Point	°C	ASTM D97	-20

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."