

INDUSTRIAL WHITE 150 VG20



INDUSTRIAL RANGE

28 products | 10 ISO VG grades

ISO VG 20	1	ISO VG 32	2
ISO VG 46	2	ISO VG 68	5
ISO VG 100	1	ISO VG 150	4
ISO VG 220	3	ISO VG 320	2
ISO VG 460	2	ISO VG 680	2

SPECIFICATIONS ISO VG 20

US FDA21-CFR 178.3620B US FDA21-CFR 178.3620 A
US FDA21-CFR 178.3570 US FDA21-CFR 172.878

Highly Refined White Oil for Documented Industrial and Agri-Food Applications

Highly refined white oil, from which aromatic compounds, sulphur and nitrogen have been removed, according to the source. For documented industrial and agri-food uses.

Key Advantages:

- High chemical and oxidative stability
- High hydrolytic stability
- High thermal stability



AVAILABLE PACKING

20 L	208 L
1.000 L	

INDUSTRIAL

INDUSTRIAL WHITE 150 VG20

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	840
Kinematic viscosity at 40°C	cSt	ASTM D445	20
Kinematic viscosity at 100°C	cSt	ASTM D445	4,13
Viscosity index	-	ASTM D2270	105
Flash Point	°C	ASTM D92	225
Pour Point	°C	ASTM D97	-12

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."