

NEOVIA 0W-12 HPF



AURIN RANGE

14 products | 8 SAE grades

SAE 0W-8	1	SAE 0W-12	1
SAE 0W-16	1	SAE 0W-20	1
SAE 0W-30	1	SAE 5W-30	1
SAE 5W-40	2	SAE 75W-70	1

SPECIFICATIONS SAE 0W-12

SAE J300

HTHS ≥ 2.0 mPa·s

Low-Friction Fully Synthetic Lubricant for Hybrid Petrol Engines & Range Extenders

Low-friction, fully synthetic SAE 0W-12 for compatible hybrid petrol engines and range extender systems. It is geared towards energy-efficient operation and lubrication during repeated engine starts and stops. HTHS ≥ 2.0 mPa·s.

Key Advantages:

- Low-friction SAE 0W-12 formulation
- Supports energy-efficient operation
- Lubrication during repeated engine starts and stops
- HTHS ≥ 2.0 mPa·s



AVAILABLE PACKING

1 L

5 L

AURIN

NEOVIA 0W-12 HPF

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density	kg/m ³	ASTM D7042	847
Kinematic viscosity at 40°C	cSt	ASTM D445	33.7
Kinematic viscosity at 100°C	cSt	ASTM D445	6.4
Viscosity Index	-	ASTM D2270	145
Flash Point	°C	ASTM D92	226
Freezing point	°C	ASTM D97	-46

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."