

PERFORMANCE 10W-30 SP



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 10W-30

API SP/SN-PLUS/CF
 ILSAC GF-6A
 GM 6094M
 CHRYSLER MS-6395

Hydroisomerised-Base Lubricant for Direct-Injection Petrol Engines

SAE 10W-30 lubricant with a hydroisomerised base for direct-injection petrol engines that require this viscosity grade. The additive technology is geared towards LSPI control, protection against wear and limiting deposits.

Key Advantages:

- Effective counteraction of LSPI (Low-Speed Pre-Ignition)
- Outstanding oxidation stability
- High dispersancy
- High anti-corrosion, anti-rust and cleaning properties



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

PERFORMANCE 10W-30 SP

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,86
Kinematic viscosity at 40°C	cSt	ASTM D445	69
Kinematic viscosity at 100°C	cSt	ASTM D445	10,9
Viscosity Index	-	ASTM D2270	149
Flash Point	°C	ASTM D92	231
Freezing point	°C	ASTM D97	-31

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."