

PERFORMANCE 10W-40



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 10W-40

API SN/CF	VW 502.00
ACEA A3/B4	VW 505.00
MB 229.1	RENAULT RN 0700 RN 0710
MB 229.3	PSA B712300
MB 229.5	FIAT 9.55535-G2
MB 226.5	FIAT 9.55535-D2
VW 501.00	

Group III Lubricant for Petrol & Diesel Engines in Everyday Use

SAE 10W-40 lubricant with hydroisomerised Group III base oils for compatible petrol and diesel engines. It focuses on maintaining the lubricating film and protecting internal mechanical surfaces during everyday operation.

Key Advantages:

- Effective resistance to lubricant oxidation
- High thermal stability
- Superior detergency
- Dispersant, anti-corrosion and anti-rust properties



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

PERFORMANCE 10W-40

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,86
Kinematic viscosity at 40°C	cSt	ASTM D445	93,6
Kinematic viscosity at 100°C	cSt	ASTM D445	14,1
Viscosity Index	-	ASTM D2270	155
Flash Point	°C	ASTM D92	231
Freezing point	°C	ASTM D97	-31

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."