

PERFORMANCE 15W-40



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 15W-40

API SN/CF
 ACEA A3/B4
 MB 229.1
 MB 226.5
 VW 501.01/505.00
 RN 0710 RN 0700
 PSA B712295

Mineral Multigrade Lubricant for Older Petrol & Diesel Cars and Light Commercial

Multigrade SAE 15W-40 lubricant with a paraffinic mineral base for compatible petrol and diesel engines, particularly of older passenger cars and light commercial vehicles. Intended to protect mechanical parts in everyday and prolonged operation.

Key Advantages:

- High detergency
- Acid-neutralising function
- Protection of mechanical components
- Prevention of sludge and emulsions



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

PERFORMANCE 15W-40

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,862
Kinematic viscosity at 40°C	cSt	ASTM D445	104
Kinematic viscosity at 100°C	cSt	ASTM D445	14,9
Viscosity Index	-	ASTM D2270	149
Flash Point	°C	ASTM D92	231
Freezing point	°C	ASTM D97	-28

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."