

MAX SPEED

TECHNICAL DATA SHEET

RACEFORCE 15W-60



MAX SPEED RANGE

19 products | 13 SAE grades

SAE 5W	1	SAE 5W-40	1
SAE 5W-50	1	SAE 10W	1
SAE 10W-40	1	SAE 10W-50	1
SAE 10W-60	1	SAE 15W	1
SAE 15W-40	1	SAE 15W-50	1
SAE 15W-60	1	SAE 20W-40	1
SAE 20W-50	1		

SPECIFICATIONS SAE 15W-60

API SP/ SN/SM

JASO T903 JASO MA-MA2

JASO Quality Category SP

Four-Stroke Motorcycle Engine Oil SAE 15W-60 for Road Bikes & Recreational Vehicles

SAE 15W-60 lubricant for four-stroke road motorcycle engines and selected ATV, SXS or other recreational vehicle applications where this category is specified. Designed for demanding operating conditions. Suitability for wet clutches and the JASO specification must be consistent with the owner's manual and the current TDS.

Key Advantages:

- Maximum heat dissipation
- Excellent oxidation stability
- High resistance to pre-ignition
- Low pour point and very high viscosity index, ensuring maximum protection even with extreme temperature fluctuations
- High detergent, anti-corrosion and anti-rust properties



AVAILABLE PACKING

1 L	4 L
20 L	60 L
208 L	1.000 L

MAX SPEED

RACEFORCE 15W-60

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,866
Kinematic viscosity at 40°C	cSt	ASTM D445	198,25
Kinematic viscosity at 100°C	cSt	ASTM D445	24,6
Viscosity index	-	ASTM D2270	155
Flash Point	°C	ASTM D92	233
Pour point	°C	ASTM D97	-27

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."