MAX SPEED

TECHNICAL DATA SHEET

RACEFORCE FX 540

MAX SPEED RANGE

19 products | 13 SAE grades

SAE 5W	1	SAE 5W-40	1
SAE 5W-50	1	SAE 10W	1
SAE 10W-40	1	SAE 10W-50	1
SAE 10W-60	1	SAE 15W	1
SAE 15W-40	1	SAE 15W-50	1
SAE 15W-60	1	SAE 20W-40	1
SAE 20W-50	1		

SPECIFICATIONS

API SP/SN/SM
JASO T903
JASO MA/MA2
SAE 5W-40

Synthetic Four-Stroke Motorcycle Engine Oil SAE 5W-40 for Road & Demanding Use

Synthetic SAE 5W-40 lubricant for four-stroke engines of road motorcycles and demanding applications. Intended for engine lubrication and, where the vehicle documentation permits, a shared transmission/wet-clutch circuit. Selection is based on the viscosity grade and specification required by the manufacturer.

Key Advantages:

- Maximum heat dissipation
- Excellent oxidation stability
- High resistance to pre-ignition
- Low pour point and very high viscosity index, ensuring maximum protection even with extreme temperature fluctuations
- High detergent, anti-corrosion and anti-rust properties

RED LUBRICANTS
Feel The Difference

AVAILABLE PACKING

1 L 5 L

MAX SPEED

RACEFORCE FX 540

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm³	ASTM D7042	0,855
Kinematic viscosity at 40°C	cSt	ASTM D445	91,4
Kinematic viscosity at 100°C	cSt	ASTM D445	15,5
Viscosity index	-	ASTM D2270	181
Flash Point	°C	ASTM D92	226
Pour point	°C	ASTM D97	-41

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.

RED LUBRICANTS
Feel The Difference

“Blended with British Traditional Crafts.”