

SEA-TECH 20W-50 4T



MARINE 2T - 4T RANGE

6 products | 3 SAE grades

SAE 10W-30	2	SAE 15W-40	1
SAE 20W-50	1		

SPECIFICATIONS SAE 20W-50

API CI-4	MERCURY-MARINE
ACEA E7	MERCURISER RACING V8
VOLVO VDS-3	HONDA-MARINE SUZUKI-
MB 228.3	MARINE
MTU	VOLVO PENTA V6 /V8
CAT Type 2.1	CHRYSLER MARINE
CATERPILLAR ECF-3	YAMAHA RIVA CRUSADER
RN RLD-3	

High-Performance Marine Diesel Engine Oil SAE 20W-50

High-performance SAE 20W-50 lubricant for naturally aspirated or turbocharged diesel engines in marine applications. It is designed for demanding operation at medium and high engine speeds, under prolonged loads, high pressures and temperatures, in accordance with the manufacturer's requirements.

Key Advantages:

- Excellent thermo-oxidative resistance
- Maximum thermal stability
- Counteracts fouling, lacquer and sludge
- High anti-corrosion, anti-rust and dispersant properties
- Prevention of carbon deposits on the pistons



AVAILABLE PACKING

1 L	4 L
20 L	60 L
208 L	1.000 L

MARINE 2T - 4T

SEA-TECH 20W-50 4T

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,87
Kinematic viscosity at 40°C	cSt	ASTM D445	140
Kinematic viscosity at 100°C	cSt	ASTM D445	19,5
Viscosity index	-	ASTM D2270	160
Flash Point	°C	ASTM D92	233
Pour point	°C	ASTM D97	-28

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."