

ULTRA LS 80W-90



GEAR LUBE RANGE

9 products | 6 SAE grades

SAE 75W	1	SAE 75W-80	2
SAE 75W-90	2	SAE 75W-140	1
SAE 80W-90	2	SAE 85W-90	1

SPECIFICATIONS SAE 80W-90

API GL-5 LSMT -1 GL4
MIL – L 2105 D SAE J-2360
ZF TE-ML 05C/12C/21C

Gear Lubricant for Limited-Slip Differentials of Cars, SUVs & Commercial Vehicles

SAE 80W-90 lubricant for compatible limited-slip differentials (LS/LSD) of passenger cars, SUVs and commercial vehicles. Its specialised use requires confirmation of the differential manufacturer's requirements.

Key Advantages:

- Optimised performance thanks to the correct coefficient of friction value
- Very high thermal and oxidative stability
- Exceptional friction control
- Maximum resistance to wear
- Maximum compatibility with materials used in these systems



AVAILABLE PACKING

1 L	4 L
20 L	60 L
208 L	

GEAR LUBE

ULTRA LS 80W-90

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,890
Kinematic viscosity at 40°C	cSt	ASTM D445	133
Kinematic viscosity at 100°C	cSt	ASTM D445	15
Viscosity Index	-	ASTM D2270	115
Flash Point	°C	ASTM D92	237
Pour Point	°C	ASTM D97	-28

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."