

VELOX 0W-16 HPF



AURIN RANGE

14 products | 8 SAE grades

SAE 0W-8	1	SAE 0W-12	1
SAE 0W-16	1	SAE 0W-20	1
SAE 0W-30	1	SAE 5W-30	1
SAE 5W-40	2	SAE 75W-70	1

SPECIFICATIONS SAE 0W-16

API SP
ILSAC GF-6b
SAE J300
HTHS $\geq 2.3 \text{ mPa}\cdot\text{s}$

Fully Synthetic Low-Friction Lubricant for Hybrid Petrol Engines & Range Extenders

Fully synthetic SAE 0W-16 lubricant for compatible petrol engines of HEV, PHEV and MHEV hybrids, as well as range extenders. The low-friction formulation is intended for operation with frequent starts and stops, supporting energy efficiency. HTHS $\geq 2.3 \text{ mPa}\cdot\text{s}$.

Key Advantages:

- Low-friction SAE 0W-16 formulation
- Designed for operation with frequent starts and stops
- Supports energy efficiency
- HTHS $\geq 2.3 \text{ mPa}\cdot\text{s}$



AVAILABLE PACKING

1 L

5 L

AURIN

VELOX 0W-16 HPF

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density	kg/m ³	ASTM D1298	848
Kinematic viscosity at 40°C	cSt	ASTM D445	36.7
Kinematic viscosity at 100°C	cSt	ASTM D445	7.1
Viscosity Index	-	ASTM D2270	160
Flash Point	°C	ASTM D92	226
Freezing point	°C	ASTM D97	-45

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."