

VOLTRIA HV



AURIN RANGE

14 products | 8 SAE grades

SAE 0W-8	1	SAE 0W-12	1
SAE 0W-16	1	SAE 0W-20	1
SAE 0W-30	1	SAE 5W-30	1
SAE 5W-40	2	SAE 75W-70	1

SPECIFICATIONS

VOLVO C40 Recharge
VOLVO XC40 EX40
PININFARINA BATTISTA Hyper
GT Elettrica
RIVIAN R1S
RIVIAN R1T
RIMAC NEVERA
JAGUAR I-PACE

JAGUAR E-PACE PLUG-IN
HYBRID (PHEV)
POLESTAR2
BYD EV
NIO ET7 ES6 EC6 ES8
MG4 Elettric Standard
WELTMEISTER 6

Fully Synthetic Fluid for Electric Vehicle Transmissions (HV Version)

Fully synthetic special transmission fluid for electric vehicles, in the HV version of the VOLTRIA family. It is geared towards lubrication and protection of mechanical parts, thermo-oxidative stability and heat management. Electrical properties and suitability are determined by the application's specifications.

Key Advantages:

- Protection against wear
- High thermo-oxidative stability
- Smooth and synchronised engagement



AVAILABLE PACKING

1 L

5 L

AURIN

VOLTRIA HV

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Density at 15°C	kg/m ³	ASTM D1298	848
Kinematic viscosity at 40°C	cSt	ASTM D445	28,2
Kinematic viscosity at 100°C	cSt	ASTM D445	6,2
Viscosity Index	-	ASTM D2270	180
Flash Point	°C	ASTM D92	224
Pour Point	°C	ASTM D97	-52
Viscosity at -40°C	mPa·s	ASTM D2983	7500

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."