

ZENITH 0W-16



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 0W-16

API SP
ILSAC GF-6B

Fully Synthetic Very-Low-Viscosity Lubricant for Modern Petrol & Hybrid Engines

Fully synthetic, very-low-viscosity SAE 0W-16 lubricant for modern petrol engines, including compatible hybrids. The low-friction formulation supports fuel economy, LSPI control, oxidation stability and the limitation of deposits. HTHS ≥ 2.3 mPa·s.

Key Advantages:

- High energy efficiency and reduced fuel consumption
- Effective action against LSPI (Low-Speed Pre-Ignition)
- Low friction coefficient
- High oxidation stability at the high operating temperatures of modern turbocharged engines
- Excellent detergency and dispersancy



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

ZENITH 0W-16

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,840
Kinematic viscosity at 40°C	cSt	ASTM D445	35,2
Kinematic viscosity at 100°C	cSt	ASTM D445	7,2
Viscosity Index	-	ASTM D2270	175
Flash Point	°C	ASTM D92	215
Freezing point	°C	ASTM D97	-47

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."