

ZENITH 0W-30 12FE



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 0W-30

API SP/SN PLUS	MB 229.61
ACEA C2	MB 227.61
BMW LL-12FE	FORD WSS-M2C920-A
BMW 83212365935	FIAT 9.55535-GS1
BMW 83212405666	FIAT 9.55535-DS1
BMW 83212405097	VOLVO VCC 95200377

Synthetic Low-Friction Lubricant for Engines Requiring Longlife-12 FE

Synthetic SAE 0W-30 lubricant for specific BMW engines that call for BMW Longlife-12 FE. Designed with a focus on low friction and energy-efficient operation, only in applications where this specification is permitted by the manufacturer.

Key Advantages:

- High energy efficiency and reduced fuel consumption
- Low friction coefficient
- High oxidation stability at the high operating temperatures of modern turbocharged engines
- Low pour point and very high viscosity index for protection across wide temperature changes



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

ZENITH 0W-30 12FE

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,847
Kinematic viscosity at 40°C	cSt	ASTM D445	64,2
Kinematic viscosity at 100°C	cSt	ASTM D445	11,5
Viscosity Index	-	ASTM D2270	176
Flash Point	°C	ASTM D92	227
Freezing point	°C	ASTM D97	-42

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."