

ZENITH 5W-20 SP



HEPHAESTUS RANGE

34 products | 16 SAE grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS SAE 5W-20

API SP/SN PLUS/SN-RC	TOYOTA
ACEA C5	FORD WSS-M2C925-A/B
ILSAC GF-6A	FORD WSS-M2C930-A/B
GM dexos1 Gen2	FORD WSS-M2C945-A
JAGUAR LAND	FORD WSS-M2C948-B1
ROVER	FORD WSS-M2C960-A1
STJLR 03.5004	FIAT 9.55535-CR1
HONDA	CHRYSLER MS-6395
SUZUKI	

Synthetic Lubricant for Small Direct-Injection Turbocharged Petrol Engines

Synthetic SAE 5W-20 lubricant with an API SP reference for modern small-displacement, direct-injection and turbocharged petrol engines. The additive technology focuses on LSPI control and on engine protection during operation under load.

Key Advantages:

- Effective LSPI (Low-Speed Pre-Ignition) control
- Excellent oxidation stability at the high operating temperatures of modern turbocharged engines
- Excellent anti-wear performance for metals and alloys, reducing friction
- Low pour point and very high viscosity index for protection across severe temperature changes



AVAILABLE PACKING

1 L	4 L
5 L	20 L
60 L	208 L
1.000 L	

HEPHAESTUS

ZENITH 5W-20 SP

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,851
Kinematic viscosity at 40°C	cSt	ASTM D445	49,3
Kinematic viscosity at 100°C	cSt	ASTM D445	8,9
Viscosity Index	-	ASTM D2270	162
Flash Point	°C	ASTM D92	226
Freezing point	°C	ASTM D97	-37

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."