

ZF ATF



TRANSOFT RANGE

8 products

SPECIFICATIONS

ZF TE-ML 04D
ZF TE-ML 14E
ZF TE-ML 16N
ZF TE-ML 20G/20E/20F
ZF TE-ML 25F
SFU
MAN 339 Tipo Z4 ECOMAT / Z13 ECOLIFE
SFU IVECO IRISBUS ECOMAT/ECOLIFE

High-Performance Synthetic Fluid for Bus & Heavy-Duty Automatic Transmissions

High-performance synthetic fluid for compatible ZF Ecomat and Ecolife automatic transmissions in buses and heavy vehicles. Designed for continuous operation, stop-and-go traffic and high thermal stress, with emphasis on thermo-oxidative stability and friction control. Drain intervals follow exclusively the manufacturer's instructions.

Key Advantages:

- Very high thermal and oxidative stability
- High heat exchange coefficient for effective cooling
- Exceptional friction control
- Maximum resistance to wear
- Maximum compatibility with materials used in these systems



AVAILABLE PACKING

1 L	4 L
20 L	60 L

TRANSOFT

ZF ATF

TECHNICAL DATA SHEET

Typical Characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	kg/dm ³	ASTM D7042	0,841
Kinematic viscosity at 40°C	cSt	ASTM D445	59
Kinematic viscosity at 100°C	cSt	ASTM D445	10,2
Viscosity Index	-	ASTM D2270	162
Flash Point	°C	ASTM D92	241
Pour Point	°C	ASTM D97	-54

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



"Blended with British Traditional Crafts."